AUTHOR: Hans Walden,
Analytical Chemist

EFF. DATE: 5-31-06

NUMBER 23A*(NON-GE)*

APPROVED: Mike Ziegler,
Plant Manager

PAGES 1 of 1

CONTROLLED COPY

SUPERSEDE NEW

MANUAL TYPE: CHEMICAL PRODUCT SPECIFICATION

PRODUCT: SODIUM TRICHLOROBENZENESULFONATE (STB)

PARAMETER	***LIMITS***	***TEST METHOD***
UNCOATED MATERIAL		
Sodium Sulfate, %	*2 Max*	*109*
APHA Color	*25*	*110*
pH_A and pH_B	*7.0 ± 0.4*	*111*
Water, %	*9.0 Max*	*AR.CQC.012*
*Iron, ppm**	*10 Max*	*106*
*Sieve Test***	*65% of powdered STB passes a No. 40 Sieve, Max. of 2% retained by a No. 20 Sieve.*	
Appearance	*White Powder*	*Visual*

***IR Scan to be run on each lot for reference, not to be reported on C of A.*

COATED MATERIAL

Coating Applied	*1%*	*Based on Weight*

**Note: Material with 10-15 ppm iron may be blended with lower iron product provided final blend is 10 ppm maximum. Materials with iron levels above 15 ppm may not be blended without approval of appropriate General Electric Raw Material Quality representative.*

***Note: Not reported or shown on C of A unless customer request.*